8820 Old Hwy 99 SE, Tumwater, Washington 98501, USA 360-943-6063 800-562-6184 FAX 360-352-4813 www.ch2o.com

Product Bulletin

WAX-AWAY

HEAVY-DUTY WAX & GREASE REMOVER
A CONCENTRATED CLEANER DESIGNED OT REMOVE WAX BUILDUPS ON
CONVEYORS, DRYERS, ROLLERS, BRUSHES & OTHER PROCESSING EQUIPMENT

TYPICAL APPLICATIONS

WAX-AWAY is recommended for use on conveyors, framework, augers, mixers, tile walls, floors, and general food processing equipment.

<u>WAX-AWAY</u> is designed for the removal of grease, wax, and oily films on food processing equipment and structures. <u>WAX-AWAY</u> can be used on soft metals and is effective on tile, rubber, and plastic surfaces.

CONCENTRATED

WAX-AWAY's heavy-duty formulation allows low usesolution concentrations, resulting in low cost cleaning with optimum performance.

CONVENIENT

Because **WAX-AWAY** is a liquid cleaner, it can be dispensed accurately and efficiently through automatic feed/control systems.

MODERATE FOAMER

WAX-AWAY provides a moderate amount of foaming to aid in soil penetration during cleaning processes, where foam may contact upper portions of conveyors and vessels.

FREE RINSING

Selected chelants and wetting agents in **WAX-AWAY** provide excellent rinsing ability and inhibit the formation of calcium carbonate (CaCO₃) precipitate in the rinse cycle.

SAFETY & HANDLING PROCEDURE

This is an alkaline product. Eye contact will cause severe irritation and/or minor burns. Prolonged or repeated skin contact can cause irritation and possible dermatitis. Excessive inhalation of product mists can cause irritation to the respiratory system. Wear impervious gloves and safety glasses or goggles when handling product

GENERAL DIRECTIONS

WAX-AWAY can be applied by manual methods as in general housekeeping operations. Dilute 1 part **WAX-AWAY** with 10 to 20 parts water at up 120°F. In high pressure spray cleaning or CIP systems, a dilution of 1 part **WAX-AWAY** per 50 to 100 parts water at 140°-160°F is recommended. When used in steam cleaning equipment, use 1:10 to 1:20. In power floor scrubbers, use ranges from 1:10 to 1:80 depending on the soil load to be removed.

PHYSICAL PROPERTIES

Appearance	Clear Blue Liquid
Odor	Slight
Foam	Moderate
Rinsing Ability	Excellent
pH of Use Solution	11.5-12.5
Pounds per Gallon	8.8-9.3

PRODUCT pH INDICATOR

---- acid ---- neutral ---- alkaline ----0 1 2 3 4 5 6 7 8 9 10 11 12 13 14



Seller Warranty

CH₂O brand test reagent refills are available through your sales representative at no charge. Customers are required to confirm product compatibility via a control test for their specific application. CH₂O recommends that you perform regular/daily testing to control chemical levels and cycles of concentration within established limits. Additional tests may be performed at your request. Test reports reflect conditions at the point when the analysis was performed. Results will change over time and with varying operating conditions.

Seller warrants that this product conforms to its chemical description and is reasonably fit for the purpose referred to in the product data sheet. Buyer is responsible to ensure that products and product dosages are appropriate for Buyer's particular application. Seller makes no other warranty or representation of any kind, express or implied, concerning the product, including NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS OF THE GOODS FOR ANY OTHER PARTICULAR PURPOSE. No such warranties shall be implied by law and no agent of seller is authorized to alter this warranty in any way except in writing with a specific reference to this warranty. The exclusive remedy against seller shall be a claim for damages not to exceed the purchase price of the product, without regard to whether such a claim is based upon breach of warranty or tort. Jurisdiction for any issues arising from or relating to this product shall be in the courts of the State of Washington and the venue shall be Thurston County. Any controversy or claim arising out of or relating to this contract, or breach thereof, shall be settled by arbitration in accordance with the rules and procedures as stated in RCW 7.06 and shall be binding upon both parties without right to appeal, and judgment upon the award rendered by the Arbitrator(s) may be entered in any court having jurisdiction thereof.

Applies to all products sold by CH₂O, Inc., and is hereby communicated to all of its customers as a condition of sale. Use of CH₂O products is subject to the Standard Terms and Conditions as listed on CH₂O, Inc.'s website at: www.ch2o.com.



