



8820 Old Hwy 99 SE, Tumwater, Washington 98501, USA
360-943-6063 800-562-6184 FAX 360-352-4813 www.ch2o.com



6247 POSCA BOILER WATER TREATMENT

APPLICATION

All natural water contains dissolved mineral salts such as calcium, magnesium and iron bicarbonate. Thermal decomposition of these bicarbonates occurs in boilers and steam generating equipment. The resulting carbonate salts are much less soluble than the bicarbonate. The result is a precipitation of the carbonates, which become hard, rigid deposits. Mineral deposition occurs on heat-transfer surfaces in a boiler. This deposition acts as insulation, lowering the heat-transfer ability of the boiler. Heat-transfer losses significantly increase fuel consumption. When extreme heat-transfer losses occur, high metal temperatures are created which cause heat stress cracking and other boiler metal damage.

Product **6247** is an aqueous blend of phosphonate, synthetic organic, sequestering, and chelating additives. These agents prevent mineral crystal formation. Highly distorted crystals are formed when chelating and sequestering components have reached their limitations. Simultaneously, the distorted crystals are separated from one another by polymeric dispersants.

Product **6247** is formulated to meet boiler operation needs for high mineral control, especially boilers where the feedwater has high mineral content. Its exceptional ability to hold high concentrations of minerals (such as calcium and magnesium) in solution prevents damage due to new mineral deposit formation. Product **6247** is a one-drum mineral control product with extra-added sulfite for chemical deaeration.

SAFETY & HANDLING PROCEDURE

This product is an alkaline liquid. It can be safely handled using the standard precautionary procedures associated with industrial chemicals of this type. Avoid prolonged or repeated contact with product. Consult the MSDS for further safety and handling procedures.

FEEDING TECHNIQUE

Pump directly into the makeup water line of the boiler or add via a one-shot or bypass feeder. It can also be added to a chemical feed tank or condensate receiver.

DOSAGE

Initially charge the system at a rate of 98 fluid ounces per 1,000 gallons of water in the system. Reduce maintenance feed rate with respect to the cycles of concentration being maintained.

CONTROL

Maintain a residual of 6 to 15 parts per million of POSCA as tested by CH₂O's **P-2** test kit, in the system at all times. Consult your CH₂O water treatment specialist for testing options and residual parameters specific to individual systems. Daily testing is recommended to maintain proper control. Failure to monitor and maintain treatment levels can cause damage. In addition to monitoring and maintaining treatment levels, it is the customer's responsibility to ensure the product is fit for its intended application.

PHYSICAL PROPERTIES

pH of 1% Solution..... >10
Pounds per Gallon..... 10.0-10.5
Physical Appearance..... Clear, Yellowish Liquid
Odor..... Mild
Flash Point..... NA

Seller Warranty

CH₂O brand test reagent refills are available through your sales representative at no charge. Customers are required to confirm product compatibility via a control test for their specific application. CH₂O recommends that you perform regular/daily testing to control chemical levels and cycles of concentration within established limits. Additional tests may be performed at your request. Test reports reflect conditions at the point when the analysis was performed. Results will change over time and with varying operating conditions.

Seller warrants that this product conforms to its chemical description and is reasonably fit for the purpose referred to in the product data sheet. Buyer is responsible to ensure that products and product dosages are appropriate for Buyer's particular application. Seller makes no other warranty or representation of any kind, express or implied, concerning the product, including NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS OF THE GOODS FOR ANY OTHER PARTICULAR PURPOSE. No such warranties shall be implied by law and no agent of seller is authorized to alter this warranty in any way except in writing with a specific reference to this warranty. The exclusive remedy against seller shall be a claim for damages not to exceed the purchase price of the product, without regard to whether such a claim is based upon breach of warranty or tort. Jurisdiction for any issues arising from or relating to this product shall be in the courts of the State of Washington and the venue shall be Thurston County. Any controversy or claim arising out of or relating to this contract, or breach thereof, shall be settled by arbitration in accordance with the rules and procedures as stated in RCW 7.06 and shall be binding upon both parties without right to appeal, and judgment upon the award rendered by the Arbitrator(s) may be entered in any court having jurisdiction thereof.

Applies to all products sold by CH₂O, Inc., and is hereby communicated to all of its customers as a condition of sale. Use of CH₂O products is subject to the Standard Terms and Conditions as listed on CH₂O, Inc.'s website at: www.ch2o.com.



VERSION DATE: May 23, 2003 REVISION DATE: February 20, 2019

